

CSP SERIES

BMB Sound everywhere, PA type speaker Tuned for valious scene use.

A new type of vocal and music mixing style. Not only for KTV, but also for Bar, Club, Restaurant, various scene.

1. Cabinet made of high quality birch plywood assembled by box joint.
The tough structure keeps outputting powerful sound stably.

2. Clear high frequency sound by fine-tuned diaphragm



NEW

CSP-612 [12"]



NEW

CSP-610 [10"]

System	2 Ways 2 Speakers Bass-Reflex	2 Ways 2 Speakers Bass-Reflex
Woofer Unit	300mm(12inch) Paper Cone Type × 1unit With 75mm(2.95inch) Coil × 1unit	250mm(10inch) Paper Cone Type × 1unit With 65mm(2.6inch) Coil × 1unit
Tweeter Unit	25mm Throat, 44.4mm Coil Diaphragm Assembly Type × 1unit	26mm Throat, 34.4mm Coil Diaphragm Assembly Type × 1unit
Freq. Response	54Hz~20.000Hz(±3dB)	60Hz~20.000Hz(±3dB)
Sensitivity	98dB/W/m	96dB/W/m
Max SPL Peak	133dB/m	128dB/m
Max SPL Continuous	127dB/m	124dB/m
Max Input Power	1600W	1200W
Rating Input Power	400W(Public Addresses speaker type)	300W(Public Addresses speaker type)
Recommended Amplifier	500W(DAD-500(SE))	500W(DAD-500(SE))
HF Protections	Poly Switch Circuit Breaker	Poly Switch Circuit Breaker
Crossover Frequency	2.6KHz	2.2KHz
Horizontal Coverage	90°	90°
Vertical Coverage	90°	90°
Connector	2 × SPK4 style	2 × SPK4 style
Impedance	8Ω	8Ω
Dimensions (mm)	378(W) × 625(H) × 408(D)	319(W) × 530(H) × 357(D)
Weight	26.7 kg per piece	16.5 kg per piece
Enclosure Material	15mm birch plywood	15mm birch plywood
Grille	6.0mm Custom Hexagon perforated steel grille	5.5mm Custom Hexagon perforated steel grille
Finish	Paint Finish	Paint Finish
Pole Mount	φ35mm bottom support base	φ35mm bottom support base



The sound is tuned to be installed various type of facility.