

CSS-1000 SERIES

Entry level PA type speakers for match various scenes

It adapts "CELESTION" compression driver. We produce BMB sound quality suitable for CLUB and KARAOKE room.

Equipped with rubber foot, it can be installed not only hanging the speaker but also stationary installation.

1. Entry level PA type speaker.

2. It can be used from KTV room to the hall with reliable sound quality.





The Tweeter

High performance, reliable compression driver with ferrite magnet.



The Tweeter

CELESTION has a history of over 100 years in speaker unit design.

Natural, Clear high-frequency reproduction, A mini size compression driver.



The Woofer

Strong bass sound with a tough aluminum frame.



Rubber foot

Various installation methods are possible, Ceiling mount, stand, stationary installation.



Rear bass reflex speaker





Woofer Unit

Tweeter Unit

Freq. Response

Max SPL Peak

Max Input Power

HF Protections

Connector

Pole Mount

Rating Input Power

Horizontal Coverage

Vertical Coverage

Dimensions (mm)

Enclosure Material

Max SPL Continuous

Recommended Amplifier



2 Ways 2 Speakers	2 Ways 2 Speakers
300mm(12inch) Paper Cone Type, With 75mm(3.0inch) Coil ×1unit	250mm(10inch) Paper Cone Type With 65mm(2.6inch) Coil × 1unit
25mm Throat,44.4mm Coil Diaphragm Assembly Type × 1unit	25mm Throat,44.4mm Coil Diaphragm Assembly Type × 1unit
50Hz~20.000Hz(±3dB)	55Hz~20.000Hz(±3dB)
98dB/W/m	96dB/W/m
133dB/m	128dB/m
127dB/m	124dB/m
1600W	1000W
400W(Public Addresses speaker type)	250W(Public Addresses speaker type)
500W(DAP-5000)	500W(DAP-5000)
Poly Switch Circuit Breaker	Poly Switch Circuit Breaker
80°	80°
60°	60°
2 × SPK4 style	2 × SPK4 style
8Ω	8Ω
380(W) × 625(H) × 387(D)	333(W) × 583(H) × 325(D)
22.9 kg per piece	18.0 kg per piece
15mm Plywood construction	15mm Plywood construction
6.0mm Custom Hexagon perforated steel grille	6.0mm Custom Hexagon perforated steel grille
Litchi effect paint finish	Litchi effect paint finish
ф36mm bottom support base	ф36mm bottom support base



